VOLUME 55
1976

# THE BELL SYSTEM TECHNICAL JOURNAL

**ADVISORY BOARD**

D. E. PROCKNOW, *President,*
*Western Electric Company, Incorporated*

W. O. BAKER, *President,*
*Bell Telephone Laboratories, Incorporated*

W. L. LINDHOLM, *President,*
*American Telephone and Telegraph Company*

**EDITORIAL COMMITTEE**

D. GILLETTE, *Chairman*

W. S. BOYLE
A. G. CHYNOWETH
C. L. COYNE
T. H. CROWLEY
W. A. DEPP
I. DORROS
W. R. HARLIN
C. B. SHARP
B. E. STRASSER
I. WELBER

**EDITORIAL STAFF**

G. E. SCHINDLER, JR., *Editor*
P. WHEELER, *Associate Editor*
J. M. SZNYTER, *Art and Production Editor*
F. J. SCHWETJE, *Circulation*

## Index and Contents

AMERICAN TELEPHONE AND TELEGRAPH COMPANY
NEW YORK

## LISTS OF ISSUES IN VOLUME 55


| | |
|---|---|
| No. 1, January | Pages 1–142 |
| No. 2, February | 143–272 |
| No. 3, March | 273–372 |
| No. 4, April | 373–502 |
| No. 5, May–June | 503–690 |
| No. 6, July–August | 691–830 |
| No. 7, September | 831–1010 |
| No. 8, October | 1011–1224 |
| No. 9, November | 1225–1444 |
| No. 10, December | 1445–1579 |

Index ..... iii
Contents ..... xv


NOTE: Words in parentheses precede words not in parentheses in the same entry. For example:

Alarms (Digital Data System)

should be read Digital Data System Alarms

# 1976 CONTENTS

## January


| | | |
|---|---|---|
| T. C. Spang | Loss-Noise-Echo Study of the Direct Distance Dialing Network | 1 |
| D. L. Duttweiler | The Jitter Performance of Phase-Locked Loops Extracting Timing From Baseband Data Waveforms | 37 |
| A. Descloux | Some Properties of the Variance of the Switch-Count Load | 59 |
| M. R. Campbell, R. E. Crochiere, and L. R. Rabiner | An Algorithmic Procedure for Designing Hybrid FIR/IIR Digital Filters | 89 |
| H. Kogelnik | Filter Response of Nonuniform Almost-Periodic Structures | 109 |
| | Contributors to This Issue | 127 |
| | B.S.T.J. Briefs: | |
| W. Y. S. Chen | A Simple Method for Estimating Five-Minute Rain-Rate Distributions Based on Available Climatological Data | 129 |
| S. H. Lin | Dependence of Rain-Rate Distribution on Rain-Gauge Integration Time | 135 |


## February


| | | |
|---|---|---|
| J. N. Denenberg | Spectral Moment Estimators: A New Approach to Tone Detection | 143 |
| N. J. A. Sloane | A Simple Description of an Error-Correcting Code for High-Density Magnetic Tape | 157 |
| I. Tatsuguchi and J. W. Gewartowski | A 10-W, 6-GHz, GaAs IMPATT Amplifier for Microwave Radio Systems | 167 |
| T. F. Storey | Design of a Microprogram Control for a Processor in an Electronic Switching System | 183 |
| A. J. Rainal | Temperature Rise at a Constriction in a Current-Carrying Printed Conductor | 233 |
| | Contributors to This Issue | 271 |

## March

| | | |
|---|---|---|
| | Bell System Centennial: One Hundred Years of Publishing on Telecommunications | 273 |
| **A. G. Bell** | Researches in Telephony | 279 |
| **M. J. Gans** | Cross Polarization in Reflector-Type Beam Waveguides and Antennas | 289 |
| **D. D. Falconer** | Jointly Adaptive Equalization and Carrier Recovery in Two-Dimensional Digital Communication Systems | 317 |
| **J. A. Lewis and J. McKenna** | The Field of a Line Charge Near the Tip of a Dielectric Wedge | 335 |
| **A. D. Wyner** | A Note on the Capacity of the Band-Limited Gaussian Channel | 343 |
| **J. E. Mazo and J. Salz** | On Optical Data Communication Via Direct Detection of Light Pulses | 347 |
| | Contributors to This Issue | 371 |

## April

| | | |
|---|---|---|
| **W. M. Boyce** | Step Response of an Adaptive Delta Modulator | 373 |
| **L. R. Rabiner R. E. Crochiere** | On the Design of All-Pass Signals With Peak Amplitude Constraints | 395 |
| **D. D. Falconer** | Analysis of a Gradient Algorithm for Simultaneous Passband Equalization and Carrier Phase Recovery | 409 |
| **V. K. Prabhu** | Spectral Occupancy of Digital Angle-Modulation Signals | 429 |
| **B. Gopinath R. P. Kurshan** | A *Touch-Tone*® Receiver-Generator With Digital Channel Filters | 455 |
| **R. P. Kurshan B. Gopinath** | Digital Single-Tone Generator-Detectors | 469 |
| | Contributors to This Issue | 497 |
| | Abstracts of Bell System Papers | 499 |

## May–June

### REMREED SWITCHING NETWORKS FOR NO. 1 AND NO. 1A ESS

| | | |
|---|---|---|
| **G. Haugk and E. G. Walsh** | System Overview | 503 |
| **W. E. Archer, K. M. Olsen, and P. W. Renaut** | Development of a Remanent Reed Sealed Contact | 511 |

| | | |
|---|---|---|
| R. J. Gashler, W. E. Archer, N. Wasserman, D. H. Yano, and R. C. Zolnoski | Remreed Switches | 537 |
| D. Danielsen and W. A. Liss | Remreed Network Electronic Control | 565 |
| J. C. Kennedy, W. A. Liss, and J. R. Smith | Remreed Line Scanner | 597 |
| H. J. Klein | Physical Design of Remreed Switching Networks | 607 |
| C. H. Klosterman and J. E. Unrue, Jr. | Transmission Design and Environmental Protection of Remreed Networks | 637 |
| T. G. Grau, E. Barzilai, R. I. Narney, R. N. Rath, D. E. Tompsett, and R. G. Whitfield | Remreed Contact and Switching Network Evaluation | 663 |
| | Contributors to This Issue | 681 |
| | Abstracts of Bell System Papers | 687 |

**July–August**

| | | |
|---|---|---|
| J. G. Evans, F. W. Kerfoot, and R. L. Nichols | Automated Network Analyzers for the 0.9- to 12.4-GHz Range | 691 |
| A. E. Rosenberg | Evaluation of an Automatic Speaker-Verification System Over Telephone Lines | 723 |
| P. Balaban | Statistical Evaluation of the Error Rate of the Fiberguide Repeater Using Importance Sampling | 745 |
| V. Ramaswamy and R. D. Standley | A Phased, Optical, Coupler-Pair Switch | 767 |
| D. Marcuse | Mode Mixing With Reduced Losses in Parabolic-Index Fibers | 777 |
| J. A. Lewis | The Boundary Layer in a Concentrated, Multicomponent Electrolyte | 803 |
| | Contributors to This Issue | 825 |
| | Abstracts of Bell System Papers | 827 |

## September


| | | |
|---|---|---|
| **D. W. Hill and S. R. Neal** | Traffic Capacity of a Probability-Engineered Trunk Group | **831** |
| **R. S. Krupp** | Analysis of Toll Switching Networks | **843** |
| **W. E. Bracker and E. R. Sears** | Test Facility for a Message-Switching System | **857** |
| **P. M. Lapsa** | Calculation of Multidisturber Crosstalk Probabilities—Application to Subscriber-Loop Gain | **875** |
| **D. Gloge** | Offset and Tilt Loss in Optical Fiber Splices | **905** |
| **C. M. Miller** | Transmission vs Transverse Offset for Parabolic-Profile Fiber Splices With Unequal Core Diameters | **917** |
| **C. M. Miller** | Laminated Fiber Ribbon for Optical Communication Cables | **929** |
| **D. Marcuse** | Microbending Losses of Single-Mode, Step-Index and Multimode, Parabolic-Index Fibers | **937** |
| **S. D. Personick** | Comparison of Equalizing and Non-equalizing Repeaters for Optical Fiber Systems | **957** |
| **R. W. Dixon** | Derivative Measurements of Light-Current-Voltage Characteristics of (Al,Ga)As Double Heterostructure Lasers | **973** |
| **V. E. Beneš** | On Kailath's Innovations Conjecture | **981** |
| | Contributors to This Issue | **1003** |
| | Abstracts of Bell System Papers | **1007** |


## October


| | | |
|---|---|---|
| **F. T. Geyling** | Basic Fluid-Dynamic Considerations in the Drawing of Optical Fibers | **1011** |
| **A. H. Cherin and P. J. Rich** | An Injection-Molded Plastic Connector for Splicing Optical Cables | **1057** |
| **R. E. Crochiere, S. A. Webber, and J. L. Flanagan** | Digital Coding of Speech in Sub-bands | **1069** |
| **D. J. Goodman, B. J. McDermott, and L. H. Nakatani** | Subjective Evaluation of PCM Coded Speech | **1087** |
| **S. H. Lin** | Rain-Rate Distributions and Extreme-Value Statistics | **1111** |

| | | |
|---|---|---|
| B. W. Stuck | Distinguishing Stable Probability Measures—Part I: Discrete Time | 1125 |
| B. W. Stuck | Distinguishing Stable Probability Measures—Part II: Continuous Time | 1183 |
| G. S. Fang | Alarm Statistics of the Violation Monitor and Remover | 1197 |
| | Contributors to This Issue | 1219 |
| | Abstracts of Bell System Papers | 1221 |

**November**

| | | |
|---|---|---|
| J. B. Lastovka | An Optical Apparatus for Very-Small-Angle Light Scattering —Design, Analysis, and Performance | 1225 |
| D. Marcuse | Exact Theory of TE-Wave-Scattering From Blazed Dielectric Gratings | 1295 |
| J. R. Cavanaugh, R. W. Hatch, and J. L. Sullivan | Models for the Subjective Effects of Loss, Noise, and Talker Echo on Telephone Connections | 1319 |
| M. R. Sambur and N. S. Jayant | Speech Encryption by Manipulations of LPC Parameters | 1373 |
| D. C. Rife and R. R. Boorstyn | Multiple Tone Parameter Estimation From Discrete-Time Observations | 1389 |
| F. K. Hwang | On the Rearrangeability of Some Multistage Connecting Networks | 1411 |
| A. N. Netravali and R. Saigal | Optimum Quantizer Design Using a Fixed-Point Algorithm | 1423 |
| | Contributors to This Issue | 1437 |
| | Abstracts of Bell System Papers | 1441 |

**December**

| | | |
|---|---|---|
| D. Marcuse | Steady-State Losses of Optical Fibers and Fiber Resonators | 1445 |
| D. Marcuse | Scattering and Absorption Losses of Multimode Optical Fibers and Fiber Lasers | 1463 |
| J. A. Arnaud and R. M. Derosier | Novel Technique for Measuring the Index Profile of Optical Fibers | 1489 |

| | | |
|---|---|---|
| **L. G. Cohen, H. W. Astle, and I. P. Kaminow** | Wavelength Dependence of Frequency-Response Measurements in Multimode Optical Fibers | **1509** |
| **H. M. Presby** | Geometrical Uniformity of Plastic Coatings on Optical Fibers | **1525** |
| **A. N. Netravali, F. W. Mounts, and E. G. Bowen** | Ordering Techniques for Coding of Two-Tone Facsimile Pictures | **1539** |
| **B. R. LaCava, W. D. Miller, and B. Yaged** | Last-Trunk-Usage Measurements in Step-by-Step Switching Systems | **1553** |
| | Contributors to This Issue | **1573** |
| | Abstracts of Bell System Papers | **1577** |

# Index to Volume 55


## A

ABSORPTION AND SCATTERING LOSSES (MULTIMODE OPTICAL FIBERS AND FIBER LASERS) 1463–88

*Abstracts of Papers by Bell System Authors Published in Other Journals* 499–501 687–9, 827–30, 1007–10, 1221–4, 1441–3, 1577–9

ADAPTIVE DELTA MODULATOR (STEP RESPONSE) 373–93

ADAPTIVE EQUALIZATION AND CARRIER RECOVERY IN TWO-DIMENSIONAL DIGITAL COMMUNICATIONS SYSTEMS 317–34

ADM *See* ADAPTIVE DELTA MODULATOR

*Alarm Statistics of the Violation Monitor and Remover* 1197–217

(Al, Ga)As DOUBLE-HETEROSTRUCTURE LASERS )DERIVATIVE MEASUREMENTS OF LIGHT-CURRENT-VOLTAGE CHARACTERISTICS) 973–80

ALGORITHM
(Fixed-Point, Optimum Quantizer Design Using) 1423–35
(Gradient, Analysis for Simultaneous Passband Equalization and Carrier Phase Recovery) 409–28

*Algorithmic Procedure for Designing Hybrid FIR/IIR Digital Filters (An)* 89–108

ALGORITHMS FOR CODING OF TWO-TONE PICTURES 1539–52

ALL-PASS SIGNALS WITH PEAK AMPLITUDE CONSTRAINTS (DESIGN OF) 395–407

ALMOST-PERIODIC NONUNIFORM STRUCTURES (FILTER RESPONSE) 109–26

ANALOG AND DIGITAL NETWORKS (ECHO CONTROL, DIRECT DISTANCE DIALING) 1–36

*Analysis of a Gradient Algorithm for Simultaneous Passband Equalization and Carrier Phase Recovery* 409–28

*Analysis of Toll Switching Networks* 843–56

ANALYZERS FOR 0.9- TO 12.4-GHz RANGE (AUTOMATED NETWORK) 691–721

ANGLE-MODULATION SIGNALS (DIGITAL, SPECTRAL OCCUPANCY OF) 429–53

ANTENNAS AND BEAM WAVEGUIDES (REFLECTOR-TYPE, CROSS POLARIZATION IN) 289–316

Archer, W. E. 511–35, 537–64

Arnaud, J. A. 1489–508

Astle, H. W. 1509–23

*Automated Network Analyzers for the 0.9- to 12.4-GHz Range* 691–721

AUTOMATIC SPEAKER-VERIFICATION SYSTEM OVER TELEPHONE LINES (EVALUATION) 723–44

## B

Balaban, P. 745–66

BAND-LIMITED GAUSSIAN CHANNEL CAPACITY 343–6

Barzilai, E. 663–80

BASEBAND DATA WAVEFORMS (JITTER PERFORMANCE OF PHASE-LOCKED LOOPS EXTRACTING TIMING FROM) 37–58

*Basic Fluid-Dynamic Considerations in the Drawing of Optical Fibers* 1011–56

BEAM WAVEGUIDES AND ANTENNAS (REFLECTOR-TYPE, CROSS POLARIZATION IN) 289–316

Bell, A. G. 279–88

Bell System Centennial: *100 Years of Publishing on Telecommunications* (Editorial) 273–6

Beneš, V. E. 981–1001

BINARY, DILUTE ELECTROLYTE (BOUNDARY LAYER IN) 803–24

BISCOM (TEST MESSAGE FORMAT AND MESSAGE SWITCHING SYSTEM) 857–73

BLACK AND WHITE FACSIMILE PICTURES (ORDERING TECHNIQUES FOR CODING) 1539–52

BLAZED DIELECTRIC GRATINGS (EXACT THEORY OF TE-WAVE SCATTERING FROM) 1295–317

BLOCKING CALCULATIONS (THREE-STAGE NETWORK) 843–56

BLOCKING MEASUREMENTS (AVERAGE CALCULATIONS FOR PROBABILITY-ENGINEERED TRUNK GROUPS) 831–42

Boorstyn, R. R. 1389–410

*Boundary Layer in a Concentrated, Multicomponent Electrolyte (The)* 803–24

BOUNDARY LAYER IN DILUTE, BINARY ELECTROLYTE 803–24

Bowen, E. G. 1539–52

Boyce, W. M. 373–93

Bracker, W. E. 857–73

BUSINESS INFORMATION SYSTEMS COMMUNICATION SYSTEM *See* BISCOM

## C

CABLES
(Optical, Injection-Molded Plastic Connector for Splicing) 1057–67
(Optical Communication, Laminated Fiber Ribbon for) 929–35

*Calculation of Multidisturber Crosstalk Probabilities—Application to Subscriber-Loop Gain* 875–903

Campbell, M. R. 89–108

*Capacity of the Band-Limited Gaussian Channel (A Note on the)* 343–6

CARRIER PHASE RECOVERY AND SIMULTANEOUS PASSBAND EQUALIZATION (ANALYSIS OF GRADIENT ALGORITHM FOR) 409–28
CARRIER RECOVERY AND EQUALIZATION IN TWO-DIMENSIONAL DIGITAL COMMUNICATION SYSTEMS (JOINTLY ADAPTIVE) 317–34
Cavanaugh, J. R. 1319–71
CHANNEL CAPACITY (BAND-LIMITED GAUSSIAN) 343–6
CHANNEL FILTERS (DIGITAL, *Touch-Tone*® RECEIVER-GENERATOR WITH) 455–67
Chen, W. Y. S. 129–34
Cherin, A. H. 1057–67
CLIMATOLOGICAL DATA USED FOR ESTIMATING FIVE-MINUTE POINT RAIN-RATE DISTRIBUTIONS 129–34
COATINGS ON OPTICAL FIBERS (PLASTIC, GEOMETRICAL UNIFORMITY OF) 1525–37
CODED SPEECH (PCM, SUBJECTIVE EVALUATION) 1087–109
CODING OF SPEECH IN SUB-BANDS (DIGITAL) 1069–85
CODING OF TWO-TONE FACSIMILE PICTURES (ORDERING TECHNIQUES FOR) 1509–52
Cohen, L. G. 1509–23
COMMUNICATION CABLES (OPTICAL, LAMINATED FIBER RIBBON FOR) 929–35
COMMUNICATION SYSTEMS (TWO-DIMENSIONAL DIGITAL, JOINTLY ADAPTIVE EQUALIZATION AND CARRIER RECOVERY IN) 317–34
*Comparison of Equalizing and Nonequalizing Repeaters for Optical System Fiber Systems* 957–71
COMPUTER LANGUAGE FOR BISCOM 857–73
COMPUTER OPERATED TRANSMISSION MEASURING SET (USED WITH AUTOMATED NETWORK ANALYZERS FOR 0.9- TO 12.4-GHz RANGE) 691–721
COMPUTER PROGRAM FOR STUDY OF DEEP GRATINGS 1295–317
CONCENTRATED, MULTICOMPONENT ELECTROLYTE (BOUNDARY LAYER IN) 803–24
CONDUCTOR (CURRENT-CARRYING PRINTED, TEMPERATURE RISE AT A CONSTRICTION IN) 233–69
CONNECTING NETWORKS (MULTISTAGE, REARRANGEABILITY OF) 1411–22
CONNECTOR (INJECTION-MOLDED PLASTIC, FOR SPLICING OPTICAL CABLES) 1057–67
CONSTRICTION IN CURRENT-CARRYING PRINTED CONDUCTOR (TEMPERATURE RISE AT) 233–69
CONTACT AND SWITCHING NETWORK EVALUATION (REMREED, NO. 1 AND NO. 1A ESS REMREED SWITCHING NETWORKS) 663–80
CONTACTS (REMREED SEALED) 511–35
CONTINUOUS TIME STABLE PROBABILITY MEASURES 1183–96
CORRUGATED OPTICAL WAVEGUIDES (FILTER RESPONSE) 109–26
COTMS *See* COMPUTER OPERATED TRANSMISSION MEASURING SET
COUPLED-WAVE THEORY APPLICATION (FILTER CHARACTERISTICS OF NONUNIFORM PERIODIC WAVEGUIDES) 109–26
COUPLER-PAIR SWITCH (PHASED, OPTICAL) 767–75
Crochiere, R. E. 89–108, 395–407, 1069–85
*Cross Polarization in Reflector-Type Beam Waveguides and Antennas* 289–316
CROSSPOINTS IN REARRANGEABLE MULTISTAGE CONNECTING NETWORKS 1411–22
CROSSTALK (MULTIDISTURBER, PROBABILITY CALCULATION; APPLICATION TO SUBSCRIBER-LOOP GAIN) 875–903
CURRENT-CARRYING PRINTED CONDUCTOR (TEMPERATURE RISE AT A CONSTRICTION IN) 233–69
CURRENT-VOLTAGE-LIGHT CHARACTERISTICS OF (Al, Ga)As DOUBLE-HETEROSTRUCTURE LASERS (DERIVATIVE MEASUREMENTS) 973–80
CYCLOTOMIC FILTERS 455–67, 469–96

## D

Danielsen, D. 565–95
DATA COMMUNICATION (OPTICAL, VIA DIRECT DETECTION OF LIGHT PULSES) 347–69
DDD NETWORK *See* DIRECT DISTANCE DIALING NETWORK
DEEP GRATINGS (COMPUTER PROGRAM FOR STUDY OF) 1295–317
DELTA MODULATOR (ADAPTIVE, STEP RESPONSE) 373–93
Denenberg, J. N. 143–55
*Dependence of Rain-Rate Distribution on Rain-Gauge Integration Time* 135–41
*Derivative Measurements of Light-Current-Voltage Characteristics of (Al, Ga)As Double-Heterostructure Lasers* 973–80
Derosier, R. M. 1489–508
Descloux, A. 59–88
DESIGN (PHYSICAL, REMREED SWITCHING NETWORKS; NO. 1 AND NO. 1A ESS REMREED SWITCHING NETWORKS) 607–36
*Design of a Microprogram Control for a Processor in an Electronic Switching System* 183–232
*Design of All-Pass Signals with Peak Amplitude Constraints (On the)* 395–407
DESIGN OF OPTIMUM QUANTIZER USING FIXED POINT ALGORITHM 1423–35

Detection of Light Pulses (Optical Data Communication via) 347–69
Dielectric Gratings (Blazed, Exact Theory of TE-Wave Scattering from) 1295–317
Dielectric Sawtooth Gratings with Deep Grooves 1295–317
Dielectric Wedge (Line-Charge Field Near Tip of) 335–42
Digital and Analog Networks (Echo Control, Direct Distance Dialing) 1–36
Digital Angle-Modulation Signals (Spectral Occupancy of) 429–53
Digital Channel Filters (*Touch-Tone*® Receiver-Generator with) 455–67
*Digital Coding of Speech in Sub-bands* 1069–85
Digital Communication Systems (Two-Dimensional, Jointly Adaptive Equalization and Carrier Recovery in) 317–34
Digital Filters Design (Hybrid FIR/IIR, Algorithmic Procedure) 89–108
*Digital Single-Tone Generator-Detectors* 469–96
Digital Speech Quality 1087–109
Digital System Testing Using All-Pass Signals 395–407
Digital Tone Detector Using Spectral Moment Estimators 143–55
Dilute, Binary Electrolyte (Binary Layer in) 803–24
Direct Detection of Light Pulses (Optical Data Communication via) 347–69
Direct Distance Dialing Network
(Loss-Noise-Echo Study) 1–36
(Tone Detection Using Spectral Moment Estimators) 143–55
Discrete-Time Observations (Multiple Tone Parameter Estimation from) 1389–410
Discrete-Time Stable Probability Measures 1125–82
*Distinguishing Stable Probability Measures Part I: Discrete Time* 1125–82
*Distinguishing Stable Probability Measures Part II: Continuous Time* 1183–96
Dixon, R. W. 973–80
Double Heterostructure Lasers [(Al, Ga)As, Derivative Measurements of Light-Current-Voltage Characteristics] 973–80
Drawing of Optical Fibers (Basic Fluid-Dynamic Considerations) 1011–56
Duttweiler, D. L. 37–58

E

Earth-Satellite Radio Systems (Effect of Rain Attenuation on) 137–41
Echo-Loss-Noise Study (Direct Distance Dialing Network) 1–36
Echo Suppressors (Direct Distance Dialing Network) 1–36
Electrolyte
(Concentrated, Multicomponent; Boundary Layer in) 803–24
(Dilute, Binary; Boundary Layer in) 803–24
Electronic Control (Remreed Network, No. 1 and No. 1A ESS Remreed Switching Networks) 565–95
Electronic Switching System
(Microprogram Control Design for Processor in) 183–232
(No. 1 and No. 1A, Remreed Switching Networks for) 503–680
Encryption of Speech by Manipulations of LPC Parameters 1373–88
Environmental Protection and Transmission Design of Remreed Networks (No. 1 and No. 1A ESS Remreed Switching Networks) 637–61
Equalization and Carrier Recovery in Two-Dimensional Digital Communication Systems (Jointly Adaptive) 317–34
Equalizing and Nonequalizing Repeaters for Optical Fiber Systems (Comparison) 957–71
Error-Correcting Code for High-Density Magnetic Tape 157–65
Error Rate of Fiberguide Repeater Using Importance Sampling (Statistical Evaluation) 745–66
ESS *See* Electronic Switching System
Estimating Five-Minute Point Rain-Rate Distributions Based on Available Climatological Data 129–34
Estimation of Multiple Tone Parameters from Discrete-Time Observations 1389–410
Estimators (Spectral Moment; New Approach to Tone Detection) 143–55
*Evaluation of an Automatic Speaker-Verification System Over Telephone Lines* 723–44
Evaluation of PCM Coded Speech 1087–109
Evans, J. G. 691–721
*Exact Theory of TE-Wave Scattering from Blazed Dielectric Gratings* 1295–317
Extreme-Value Statistics and Rain-Rate Distributions 1111–24

F

Facsimile Communication Systems 1539–52

FACSIMILE PICTURES (TWO-TONE, ORDERING TECHNIQUES FOR CODING OF) 1539–52
Falconer, D. D. 317–34, 409–28
Fang, G. S. 1197–217
FIBER LASERS AND MULTIMODE OPTICAL FIBERS (SCATTERING AND ABSORPTION LOSSES) 1463–88
FIBER RESONATORS AND OPTICAL FIBERS (STEADY-STATE LOSSES) 1445–62
FIBER RIBBON (LAMINATED, FOR OPTICAL COMMUNICATION CABLES) 929–35
FIBER SPLICES
(Optical, Offset and Tilt Loss) 905–16
With Unequal Core Diameters (Parabolic-Profile, Transmission vs. Transverse Offset for) 917–27
FIBER SYSTEMS (OPTICAL, COMPARISON OF EQUALIZING AND NONEQUALIZING REPEATERS FOR) 957–71
FIBERGUIDE REPEATER ERROR RATE USING IMPORTANCE SAMPLING (STATISTICAL EVALUATION) 745–66
FIBERS
(Multimode Optical, and Fiber Lasers; Scattering and Absorption Losses) 1463–88
(Multimode Optical, Wavelength Dependence of Frequency-Response Measurements) 1509–23
(Optical, and Fiber Resonators; Steady-State Losses) 1445–62
(Optical, Basic Fluid-Dynamic Considerations in the Drawing of) 1011–56
(Optical, Geometrical Uniformity of Plastic Coatings on) 1525–37
(Optical, Novel Technique for Measuring Index Profile) 1489–508
(Parabolic-Index, Mode Mixing with Reduced Losses in) 777–802
(Step-Index Single-Mode and Parabolic-Index Multimode, Microbending Losses) 929–55
*Field of a Line Charge Near the Tip of a Dielectric Wedge (The)* 335–42
*Filter Response of Nonuniform Almost-Periodic Structures* 109–26
FILTERS
(Cyclotomic) 455–67, 469–96
(Digital, Hybrid FIR/IIR Design, Algorithmic Procedure) 89–108
(Digital Channel, *Touch-Tone*® Receiver-Generator with) 455–67
FINITE IMPULSE RESPONSE *See* FIR
FIR/IIR DIGITAL FILTERS (HYBRID, ALGORITHMIC PROCEDURE FOR DESIGNING) 89–108
FIVE-MINUTE POINT RAIN-RATE DISTRIBUTION ESTIMATE (SIMPLE METHOD BASED ON AVAILABLE CLIMATOLOGICAL DATA) 129–34
FIVE-MINUTE RAIN-RATE DISTRIBUTION (METHOD AND SOURCES FOR 20 YEARS IN U. S. A.) 131–41
FIXED-POINT ALGORITHM (OPTIMUM QUANTIZER DESIGN USING) 1423–35
Flanagan, J. L. 1069–85
FLUID-DYNAMIC CONSIDERATIONS IN THE DRAWING OF OPTICAL FIBERS (BASIC) 1011–56
FREQUENCY DOMAIN METHOD FOR MEASURING FIBER RESPONSE 1509–23
FREQUENCY-RESPONSE MEASUREMENTS IN MULTIMODE OPTICAL FIBERS (WAVELENGTH DEPENDENCE) 1509–23
FREQUENCY SHIFT KEYING USING CYCLOTOMIC FILTERS 469–96
FSK *See* FREQUENCY SHIFT KEYING

## G

GAAS, 10-W, 6-GHz IMPATT AMPLIFIER FOR MICROWAVE RADIO SYSTEMS 167–82
GAIN (SUBSCRIBER-LOOP, CALCULATION OF MULTIDISTURBER CROSSTALK PROBABILITIES) 875–903
Gans, M. J. 289–316
Gashier, R. J. 537–64
GAUSSIAN CHANNEL CAPACITY (BAND-LIMITED) 343–6
GENERATOR-DETECTORS (DIGITAL SINGLE-TONE) 469–96
GEOMETRICAL OPTICS MODEL FOR DETERMINING SPLICE LOSS 917–27
*Geometrical Uniformity of Plastic Coatings on Optical Fibers* 1525–37
Geyling, F. T. 1011–56
Gewartowski, J. W. 167–82
Gloge, D. 905–16
Goodman, D. J. 1087–109
Gopinath, B. 455–67, 469–96
GRADE OF SERVICE FOR PROBABILITY-ENGINEERED TRUNK GROUPS 831–42
GRADED MULTIPLES (DETECTING TRAFFIC CONGESTION IN) 1553–72
GRADIENT ALGORITHM FOR SIMULTANEOUS PASSBAND EQUALIZATION AND CARRIER PHASE RECOVERY (ANALYSIS) 409–28
GRATINGS (BLAZED DIELECTRIC, EXACT THEORY OF TE-WAVE SCATTERING FROM) 1295–317
Grau, T. G. 663–80

## H

Hatch, R. W. 1319–71
Haugk, G. 503–9
HIGH-DENSITY MAGNETIC TAPE (ERROR-CORRECTING CODE) 157–65
Hill, D. W. 831–42
HOLOGRAPHIC AND OPTICAL MEMORY IMAGING (USING VERY-SMALL-ANGLE LIGHT SCATTERING APPARATUS FOR) 1225–93
Hwang, F. K. 1411–22

HYBRID FIR/IIR DIGITAL FILTERS DESIGN (ALGORITHMIC PROCEDURE) 89–108

I

IBM MAGNETIC TAPE UNITS (ERROR-CORRECTING CODE) 157–65
IIR/FIR DIGITAL FILTERS (HYBRID, ALGORITHMIC PROCEDURE FOR DESIGNING) 89–108
IMPACT AVALANCHE AND TRANSIT TIME *See* IMPATT
IMPATT AMPLIFIER FOR MICROWAVE RADIO SYSTEMS (10-W, 6-GHz, GaAs) 167–82
IMPORTANCE SAMPLING (STATISTICAL EVALUATION OF ERROR RATE OF FIBERGUIDE REPEATER USING) 745–66
INDEX PROFILE OF OPTICAL FIBERS (NOVEL TECHNIQUE FOR MEASURING) 1489–508
INFINITE IMPULSE RESPONSE *See* IIR
*Injection-Molded Plastic Connector for Splicing Optical Cables (An)* 1057–67
INNOVATIONS CONJECTURE (KAILATH'S) 981–1001
INTERSYMBOL INTERFERENCE ON PERFORMANCE OF EQUALIZING AND NONEQUALIZING OPTICAL SYSTEM REPEATERS 957–71

J

Jayant, N. S. 1373–88
*Jitter Performance of Phase-Locked Loops Extracting Timing from Baseband Data Waveforms (The)* 37–58
*Jointly Adaptive Equalization and Carrier Recovery in Two-Dimensional Digital Communications System* 317–34

K

*Kailath's Innovations Conjecture (On)* 981–1001
Kaminow, I. P. 1509–23
Kennedy, J. C. 597–606
Kerfoot, F. W. 691–721
Klein, H. J. 607–36
Klosterman, C. H. 637–61
Kogelnik, H. 109–26
Krupp, R. S. 843–56
Kurshan, R. P. 455–67, 469–96

L

LaCava, B. R. 1553–72
LAMFIR *See* LAMINATED FIBER RIBBON
*Laminated Fiber Ribbon for Optical Communication Cables* 929–35
Lapsa, P. M. 875–903
LASERS
[(Al, Ga)As Double-Heterostructure, Derivative Measurements of Light-Current-Voltage Characteristics] 973–80
(Fiber, and Multimode Optical Fibers; Scattering and Absorption Losses) 1463–88
Lastovka, J. B. 1225–93
*Last-Trunk-Usage Measurements in Step-by-Step Switching Systems* 1553–72
Lewis, J. A. 335–42, 803–24
LIGHT-CURRENT-VOLTAGE CHARACTERISTICS OF (Al, Ga)As DOUBLE-HETEROSTRUCTURE LASERS (DERIVATIVE MEASUREMENTS) 973–80
LIGHT-PULSE DETECTION (OPTICAL DATA COMMUNICATIONS VIA) 347–69
LIGHT SCATTERING (VERY-SMALL-ANGLE; DESIGN, ANALYSIS AND PERFORMANCE OF OPTICAL APPARATUS FOR) 1225–93
Lin, S. H. 135–41, 1111–24
LINE-CHARGE FIELD NEAR THE TIP OF A DIELECTRIC WEDGE 335–42
LINE LINK NETWORKS (REMREED) 607–36
LINE SCANNER (REMREED, NO. 1 AND NO. 1A ESS REMREED SWITCHING NETWORKS) 597–606
LINEAR PREDICTIVE CODING *See* LPC
Liss, W. A. 565–95, 597–606
LOAD VARIANCE (SWITCH-COUNT, PROPERTIES OF) 59–88
LONG-HAUL TRANSMISSION USING IMPATT AMPLIFIERS 167–82
LONG-WAVELENGTH STUDIES USING OPTICAL APPARATUS FOR VERY-SMALL-ANGLE LIGHT SCATTERING 1225–93
LOOPS (PHASE-LOCKED, EXTRACTING TIMING FROM BASEBAND DATA WAVEFORMS, JITTER PERFORMANCE) 37–58
LOSS (OFFSET AND TILT, OPTICAL FIBER SPLICES) 905–16
LOSS, NOISE, AND TALKER ECHO ON TELEPHONE CONNECTIONS (MODELS FOR SUBJECTIVE EFFECTS OF) 1319–71
*Loss-Noise-Echo Study of the Direct Distance Dialing Network* 1–36
LOSSES
(Fiber Lasers) 1463–88
(Microbending, Single-Mode, Step-Index and Multimode, Parabolic-Index Fibers) 937–55
(Mode, Step-Index Fibers) 1463–88
(Scattering and Absorption, Multimode Optical Fibers and Fiber Lasers) 1463–88
(Steady-State, Optical Fibers and Fiber Resonators) 1445–62
LOW-PASS FILTER DESIGN (ALGORITHM FOR) 89–108

LPC Parameters (Speech Encryption by Manipulations of) 1373–88
LTU *See* Last-Trunk Usage

M

Magnetic Tape (High-Density, Error-Correcting Code) 157–65
Manipulations of LPC Parameters (Speech Encryption by) 1373–88
Marcuse, D. 777–802, 937–55, 1295–317, 1445–62, 1463–88
Maxo, J. E. 347–69
McDermott, B. J. 1087–109
McKenna, J. 335–42
Measurements in Step-by-Step Switching Systems (Last-Trunk-Usage) 1553–72
Measuring Frequency-Response Wavelength Dependence in Multimode Optical Fibers 1509–23
Measuring Optical Fiber Index Profile 1489–508
Message-Switching System (Test Facility for) 857–73
*Microbending Losses of Single-Mode, Step-Index and Multimode, Parabolic-Index Fibers* 937–55
Microprogram Control Design for Processor in Electronic Switching System 183–232
Microwave Measuring Sets 691–721
Microwave Radio-Path Engineering (Effect of Rain Rate on) 1111–24
Microwave Radio Systems (10-W, 6-GHz, GaAs IMPATT Amplifier for) 167–82
Miller, C. M. 917–27, 929–35
Miller, W. D. 1553–72
MK VI Optical Instrument (Very-Small-Angle Light Scattering Apparatus) 1225–93
Mode Coupling (Influence on Losses in Fiber Cavities) 1445–62, 1463–88
Mode Losses of Step-Index Fibers 1463–88
*Mode Mixing with Reduced Losses in Parabolic-Index Fibers* 777–802
*Models for the Subjective Effects of Loss, Noise, and Talker Echo on Telephone Connections* 1319–71
Modulation and Detection Scheme for Applying Derivative Techniques to Stripe Geometry of (Al, Ga)As Double-Heterostructure Lasers 973–80
Modulator (Adaptive Delta, . Step Response) 373–93
Monitoring Digital Transmission Systems 1197–217
Mounts, F. W. 1539–52
Multicomponent Concentrated Electrolyte (Boundary Layer in) 803–24
Multidisturber Crosstalk Probability Calculation (Application to Subscriber-Loop Gain) 875–903
Multimode Fiber Splices (Offset and Tilt Loss) 905–16
Multimode Fibers (Technique for Measuring Index Profile) 1489–508
Multimode Optical Fibers
(And Fiber Lasers, Scattering and Absorption Losses) 1463–88
(Mode Coupling) 777–802
(Steady-State Losses) 1445–62
(Wavelength Dependence of Frequency-Response Measurements in) 1509–23
Multimode, Parabolic-Index and Single-Mode, Step-Index Fibers (Microbending Losses) 929–55
*Multiple Tone Parameter Estimation from Discrete-Time Observations* 1389–410
Multiribbon Optical-Fiber Cutting Tool 1057–67
Multistage Connecting Networks (Rearrangeability of Some) 1411–22

N

Nakatani, L. H. 1087–109
Narney, R. I. 663–80
Neal, S. R. 831–42
Netravali, A. N. 1423–35, 1539–52
Network Analyzers for 0.9- to 12.4-GHz Range (Automated) 691–721
Network Electronic Control (Remreed, No. 1 and No. 1A ESS Remreed Switching Networks) 565–95
Networks
(Direct Distance Dialing, Loss-Noise-Echo Study) 1–36
(Rearrangeability of Some Multistage Connecting) 1411–22
(Remreed Line Link) 607–36
(Remreed Switching, for No. 1 and No. 1A ESS) 503–680
(Remreed Switching, Physical Design; No. 1 and No. 1A ESS Remreed Switching Networks) 607–36
(Remreed, Transmission Design and Environmental Protection; No. 1 and No. 1A ESS Remreed Switching Networks) 637–61
(Remreed Trunk Line) 607–36
(Toll Switching, Analysis) 843–56
Nichols, R. L. 691–721
No. 1 and No. 1A ESS (Remreed Switching Networks for) 503–680
No. 4 ESS Network Analysis 843–56

No. 4. Toll ESS Switching System (Direct Distance Dialing Network Echo Control) 1–36
Noise-Echo-Loss Study (Direct Distance Dialing Network) 1–36
Noise, Loss, and Talker Echo on Telephone Connections (Models for Subjective Effects of) 1319–71
Nonequalizing and Equalizing Repeaters for Optical Fiber Systems (Comparison) 957–71
Nonuniform Almost-Periodic Structures (Filter Response) 109–26
*Novel Technique for Measuring the Index Profile of Optical Fibers* 1489–508

## O

Offset (Transmission vs Transverse, for Parabolic-Profile Fiber Splices with Unequal Core Diameters) 917–27
*Offset and Tilt Loss in Optical Fiber Splices* 905–16
Olsen, K. M. 511–35
*Optical Apparatus for Very-Small-Angle Light Scattering—Design, Analysis and Performance (An)* 1225–93
Optical Cables (Splicing, Injection-Molded Plastic Connector for) 1057–67
Optical Communication Cables (Laminated Fiber Ribbon for) 929–35
*Optical Data Communication via Direct Detection of Light Pulses (On)* 347–69
Optical Fiber Coating 1525–37
Optical-Fiber Communication Systems 347–69
Optical-Fiber Cutting Tool 1057–67
Optical Fiber Splices 917–27
(Offset and Tilt Loss) 905–16
Optical Fiber Systems (Comparison of Equalizing and Nonequalizing Repeaters for) 957–71
Optical Fiber Waveguide Transmission in Communication Systems 1509–23
Optical-Fiberguide Digital-Communication System Error-Rate Calculation 745–66
Optical Fibers
(And Fiber Resonators, Steady-State Losses) 1445–62
(Basic Fluid-Dynamic Considerations in the Drawing of) 1011–56
(For Wideband Communications, Single-Mode Step-Index and Parabolic-Index Multimode) 929–55
(Geometrical Uniformity of Plastic Coatings on) 1525–37
(Laminated Fiber Ribbon) 929–35
(Mode Coupling to Minimize Losses) 777–802
(Multimode, and Fiber Lasers; Scattering and Absorption Losses) 1463–88
(Multimode, Wavelength Dependence of Frequency-Response Measurements) 1509–23
(Novel Technique for Measuring Index Profile) 1489–508
Optical Method for Evaluating Geometrical Quality of Plastic Coatings on Optical Fibers 1525–37
Optical, Phased, Coupler-Pair Switch 767–75
*Optimum Quantizer Design Using a Fixed-Point Algorithm* 1423–35
*Ordering Techniques for Coding of Two-Tone Facsimile Pictures* 1539–52
Out-of-Band Power Ratios 429–53
Overview (Remreed Switching Networks for No. 1 and No. 1A ESS) 503–9

## P

Parabolic-Index Fibers (Mode Mixing with Reduced Losses in) 777–802
Parabolic-Index Multimode and Step-Index Single-Mode Fibers (Microbending Losses) 929–55
Parabolic-Profile Fiber Splices with Unequal Core Diameters (Transmission vs Transverse Offset for) 917–27
Parameter Estimation from Discrete-Time Observations (Multiple Tone) 1389–410
Passband Equalization (Simultaneous, and Carrier Phase Recovery, Analysis of Gradient Algorithm for) 409–28
Patel-Hong Error-Correcting Code for Magnetic Tape 157–65
PCM Coded Speech (Subjective Evaluation) 1087–109
Peak Amplitude Constraints (Design of All-Pass Signals with) 395–407
Personick, S. D. 957–71
Phase-Locked Loops Extracting Timing from Baseband Data Waveforms (Jitter Performance) 37–58
*Phased, Optical, Coupler-Pair Switch (A)* 767–75
Physical Design of Remreed Switching Networks (No. 1 and No. 1A ESS Remreed Switching Networks) 607–36
Pictures (Two-Tone Facsimile, Ordering Techniques for Coding of) 1539–52
Plastic Coatings on Optical Fibers (Geometrical Uniformity of) 1525–37

Plastic-Molded Connector (Injection-Molded, for Splicing Optical Cables) 1057–67
PLL *See* Phase-Locked Loop
Prabhu, V. K. 429–53
Presby, H. M. 1525–37
Printed Conductor (Current-Carrying, Temperature Rise at a Constriction in) 233–69
Probability Calculation for Multidisturber Crosstalk (Application to Subscriber-Loop Gain) 875–903
Probability-Engineered Trunk Group (Traffic Capacity) 831–42
Probability Measures
(Stable, Continuous Time) 1183–96
(Stable, Discrete Time) 1125–82
Processor (Microprogram Control Design in Electronic Switching System) 183–232
*Properties of the Variance of the Switch-Count Load (Some)* 59–88
Publishing on Telecommunications (Bell System Centennial) 273–6
Pulse Code Modulation *See* PCM

Q

Quantizer Design Using Fixed-Point Algorithm (Optimum) 1423–35

R

Rabiner, L. R. 89–108, 395–407
Radio Path Engineering (Effect of Rain-Rate Distribution on) 135–41
Radio Systems (Microwave, 10-W, 6-GHz, GaAs IMPATT Amplifier for) 167–82
Rain Attenuation (Effect on Terrestrial and Earth-Satellite Radio Systems) 131–41
Rain-Gauge Integration Time (Dependence of Rain-Rate Distribution on) 135–41
Rain-Rate Distribution (Dependence on Rain-Gauge Integration Time) 135–41
Rain-Rate Distribution Estimate (Five-Minute Point, Simple Method Based on Available Climatological Data) 129–34
*Rain-Rate Distributions and Extreme-Value Statistics* 1111–24
Rainal, A. J. 233–69
Ramaswamy, V. 767–75
Rath, R. N. 663–80
*Rearrangeability of Some Multistage Connecting Networks (On the)* 1411–22
Receiver-Generator with Digital Channel Filters (*Touch Tone*®) 455–67
Reflector-Type Beam Waveguides and Antennas (Cross Polarization in) 289–316
Refraction Profiling Index (Using Very-Small-Angle Light Scattering Apparatus for) 1225–93
Remanent Reed Sealed Contact Development (Remreed Switching Networks for No. 1 and No. 1A ESS) 511–35
Remendur Reeds 511–35
Remreed
Contact and Switching Network Evaluation (No. 1 and No. 1A ESS Remreed Switching Networks) 663–80
Line Link Networks 607–36
Line Scanner (No. 1 and No. 1A ESS Remreed Switching Networks) 597–606
Network Electronic Control (No. 1 and No. 1A ESS Remreed Switching Networks) 565–95
Networks (Transmission Design and Environmental Protection; No. 1 and No. 1A ESS Remreed Switching Networks) 637–61
Sealed Contact Development (Remreed Switching Networks for No. 1 and No. 1A ESS) 511–35
Sealed Contact Evaluation 663–80
Switch Evaluation 663–80
Switches (Remreed Switching Networks for No. 1 and No. 1A ESS) 537–64
Switching Networks (Physical Design; No. 1 and No. 1A ESS Remreed Switching Networks) 607–36
Trunk Link Network Evaluation 663–80
Trunk Link Networks 607–36
Remreed Switching Networks for No. 1 and No. 1A ESS:
*Development of a Remanent Reed Sealed Contact* 511–35
*Physical Design of Remreed Switching Networks* 607–36
*Remreed Contact and Switching Network Evaluation* 663–80
*Remreed Line Scanner* 597–606
*Remreed Network Electronic Control* 565–95
*Remreed Switches* 537–64
*System Overview* 503–9
*Transmission Design and Environmental Protection of Remreed Networks* 637–61
Renaut, P. W. 511–35
Repeater (Fiberguide, Statistical Evaluation of Error Rate Using Importance Sampling) 745–66
Repeaters (Comparison of Equalizing and Nonequalizing for Optical Fiber Systems) 957–71
*Researches in Telephony* (Reprint, Proceedings of the American Academy of Arts and Sciences. Vol. XII. Papers Read Before the Academy.

Presented May 10, 1876, by the Corresponding Secretary) 279–88
RF Signal Band Occupancy 429–53
Ribbon (Laminated Fiber, for Optical Communication Cables) 929–35
Rich, P. J. 1057–67
Rife, D. C. 1389–410
Rosenberg, A. E. 723–44

## S

Saigal, R. 1423–35
Salz, J. 347–69
Sambur, M. R. 1373–88
Scanner (Remreed Line, No. 1 and No. 1A ESS Remreed Switching Networks) 597–606
*Scattering and Absorption Losses of Multimode Optical Fibers and Fiber Lasers* 1463–88
Scattering Losses in a Fiber Laser 1445–62
Sealed Contacts (Remreed) 511–35
Sears, E. R. 857–73
Semiconductor Contact Design 335–42
Signal Spectral Occupancy (Digital Angle-Modulation) 429–53
*Simple Description of an Error-Correcting Code for High-Density Magnetic Tape (A)* 157–65
*Simple Method for Estimating Five-Minute Point Rain-Rate Distributions Based on Available Climatological Data (A)* 129–34
Simultaneous Passband Equalization and Carrier Phase Recovery (Analysis of Gradient Algorithm for) 409–28
Single-Mode, Step-Index and Multimode, Parabolic-Index Fibers (Microbending Losses) 937–55
Single-Tone Generator-Detectors (Digital) 469–96
6-GHz, GaAs, 10-W IMPATT Amplifier for Microwave Radio Systems 167–82
Sloane, N. J. A. 157–65
Smith, J. R. 597–606
Spang, T. C. 1–36
Speaker-Verification System Over Telephone Lines (Evaluation of Automatic) 723–44
*Spectral Moment Estimators: A New Approach to Tone Detection* 143–55
*Spectral Occupancy of Digital Angle-Modulation Signals* 429–53
Speech
  Digital Coding in Sub-bands 1069–85
  (PCM Coded, Subjective Evaluation) 1087–109
  Recognition Over Telephone Lines 723–44
  Secrecy Coding 1373–88
  Verification Over Telephone Lines 723–44
*Speech Encryption by Manipulations of LPC Parameters* 1373–88
Splice Connector for Optical Cables 1057–67
Splices
  (Optical Fiber, Offset and Tilt Loss) 905–15
  (Parabolic-Profile Fiber with Unequal Core Diameters, Transmission vs Transverse Offset for) 917–27
Splicing Optical Cables (Injection-Molded Plastic Connector for) 1057–67
Stable Probability Measures
  (Continuous Time) 1183–96
  (Discrete Time) 1125–82
Standley, R. D. 767–75
*Statistical Evaluation of the Error Rate of the Fiberguide Repeater Using Importance Sampling* 745–66
Statistics of Extremes Used to Calculate High Rain Rates 1111–24
*Steady-State Losses of Optical Fibers and Fiber Resonators* 1445–62
Step-by-Step Switching Systems (Last-Trunk-Usage Measurements in) 1553–72
Step-Index Fibers (Mode Losses) 1463–88
Step-Index Single-Mode and Parabolic-Index Multimode Fibers (Microbending Losses) 929–55
*Step Response of an Adaptive Delta Modulator* 373–93
Storey, T. F. 183–232
Structures (Nonuniform Almost-Periodic, Filter Response) 109–26
Stuck, B. W. 1125–82, 1183–96
Sub-band Speech (Digital Coding) 1069–85
Subjective Effects of Loss, Noise, and Talker Echo on Telephone Connections (Models for) 1319–71
*Subjective Evaluation of PCM Coded Speech* 1087–109
Subscriber-Loop Gain (Calculation of Multidisturber Crosstalk Probabilities) 875–903
Sullivan, J. L. 1319–71
Surface Roughness Testing (Using Very-Small-Angle Light Scattering Apparatus for) 1225–93
Switch (Phased, Optical, Coupler-Pair) 767–75
Switch Codes for No. 1 ESS Line Link and Trunk Link Networks 537–64
Switch-Count Load Variance (Properties of) 59–88
Switches (Remreed, No. 1 and No. 1A ESS Remreed Switching Networks) 537–64

SWITCHING NETWORK ANALYSIS (TOLL) 843–56
SWITCHING NETWORK AND CONTACT EVALUATION (REMREED, No. 1 AND No. 1A ESS REMREED SWITCHING NETWORKS) 663–80
SWITCHING NETWORKS
For No. 1 and No. 1A ESS (Remreed) 503–680
(Remreed, Physical Design; No. 1 and No. 1A ESS Remreed Switching Networks) 607–36
SWITCHING SYSTEMS
(Electronic, Microprogram Control Design for Processor in) 183–232
(Step-by-Step, Last-Trunk-Usage Measurements in) 1553–72
SYSTEM (MESSAGE-SWITCHING, TEST FACILITY FOR) 857–73
SYSTEM OVERVIEW (REMREED SWITCHING NETWORKS FOR No. 1 AND No. 1A ESS) 503–9

## T

TALKER ECHO, LOSS, AND NOISE ON TELEPHONE CONNECTIONS (MODELS FOR SUBJECTIVE EFFECTS OF) 1319–71
Tatsuguchi, I. 167–82
TE-WAVE SCATTERING FROM BLAZED DIELECTRIC GRATINGS (EXACT THEORY OF) 1295–317
TECHNIQUE FOR MEASURING OPTICAL FIBER INDEX PROFILE 1489–508
TECHNIQUES FOR CODING OF TWO-TONE FACSIMILE PICTURES 1539–52
TELECOMMUNICATIONS PUBLISHING (BELL SYSTEM CENTENNIAL) 273–6
TELEPHONE CONNECTIONS (MODELS FOR SUBJECTIVE EFFECTS OF LOSS, NOISE, AND TALKER ECHO ON) 1319–71
TELEPHONE SWITCHING SYSTEM (PROCESSOR DESIGN) 183–232
TELEPHONE TRANSMISSION-RATING SCALE FOR USE IN NETWORK PLANNING 1319–71
TELEPHONY (RESEARCHES IN) 279–88
*Temperature Rise at a Constriction in a Current-Carrying Printed Conductor* 233–69
*10-W, 6-GHz, GaAs IMPATT Amplifier for Microwave Radio Systems* (*A*) 167–82
TERRESTRIAL RADIO SYSTEMS (EFFECT OF RAIN ATTENUATION ON) 137–41
*Test Facility for a Message-Switching System* 857–73
TEST MESSAGE FORMAT (BISCOM) 857–73
T4 VIOLATION MONITOR AND REMOVER (ALARM STATISTICS) 1197–217
THEORY OF TE-WAVE SCATTERING FROM BLAZED DIELECTRIC GRATINGS (EXACT) 1295–317
THREE-STAGE NETWORK BLOCKING CALCULATIONS 843–56
TILT AND OFFSET LOSS (OPTICAL FIBER SPLICES) 905–16
TIMING EXTRACTION FROM BASEBAND DATA WAVEFORMS (PHASE-LOCKED LOOPS JITTER) 37–58
TOLL SWITCHING NETWORK ANALYSIS 843–56
Tompsett, D. E. 663–80
TONE DETECTION (SPECTRAL MOMENT ESTIMATORS) 143–55
TONE PARAMETER ESTIMATION FROM DISCRETE-TIME OBSERVATIONS (MULTIPLE) 1389–410
Touch-Tone® *Receiver-Generator with Digital Channel Filters* (*A*) 455–67
*Touch-Tone®* SIGNALING USING CYCLOTOMIC FILTERS 469–96
*Traffic Capacity of a Probability-Engineered Trunk Group* 831–42
TRAFFIC CONGESTION (DETECTION IN GRADED MULTIPLES OF STEP-BY-STEP SWITCHING SYSTEM) 1553–72
TRAFFIC MEASUREMENT OF GRADED MULTIPLES BY LAST-TRUNK USAGE 1553–72
TRANSITION GATING FOR PHASE-LOCKED LOOPS 37–58
TRANSMISSION DESIGN AND ENVIRONMENTAL PROTECTION OF REMREED NETWORKS (No. 1 AND No. 1A ESS REMREED SWITCHING NETWORKS) 637–61
TRANSMISSION PERFORMANCE OF REMREED NETWORKS 637–61
TRANSMISSION TECHNIQUE FOR MEASURING OPTICAL FIBER INDEX PROFILE 1489–508
*Transmission vs Transverse Offset for Parabolic-Profile Fiber Splices with Unequal Core Diameters* 917–27
TRANSVERSE VS TRANSMISSION OFFSET FOR PARABOLIC-PROFILE FIBER SPLICES WITH UNEQUAL CORE DIAMETERS 917–27
TRUNK GROUP (PROBABILITY-ENGINEERED, TRAFFIC CAPACITY) 831–42
TRUNK LINK NETWORK EVALUATION (REMREED) 663–80
TRUNK LINK NETWORKS (REMREED) 607–36
TRUNK-USAGE MEASUREMENTS IN STEP-BY-STEP SWITCHING SYSTEMS 1553–72
TWO-DIMENSIONAL CORRELATION OF PICTURE SIGNALS 1539–52
TWO-DIMENSIONAL DIGITAL COMMUNICATION SYSTEMS (JOINTLY ADAPTIVE EQUALIZATION AND CARRIER RECOVERY IN) 317–34
TWO-DIMENSIONAL RECEIVER STRUCTURE 317–34

Two-Dimensional Receiver with Passband Equalization and Carrier Phase Recovery 409–28
238A Sealed Contact in Remreed Switches (No. 1 and No. 1A ESS Remreed Switching Networks) 537–64
238A Sealed Contacts 511–35
Two-Tone Facsimile Pictures (Ordering Techniques for Coding of) 1539–52

U

Uniformity of Plastic Coatings on Optical Fibers (Geometrical) 1525–37
Unrue, J. E., Jr. 637–61

V

Variance of the Switch-Count Load (Properties of) 59–88
Very-Small-Angle Light Scattering (Design, Analysis and Performance of Optical Apparatus for) 1225–93
VIA Net Loss *See* VNL
Violation Monitor and Remover (Alarm Statistics of) 1197–217
VMR *See* Violation Monitor and Remover
VNL Plan Applied to Echo Suppressors (Direct Distance Dialing Network) 1–36
Voice Identification Over Telephone Lines 723–44
Voltage-Current-Light Characteristics of (Al, Ga)As Double-Heterostructure Lasers (Derivative Measurements) 973–80
VSA Light Scattering *See* Very-Small-Angle Light Scattering

W

Walsh, E. G. 503–9
Wasserman, N. 537–64
Wave Scattering from Blazed Dielectric Gratings (TE, Exact Theory of) 1295–317
Waveforms (Baseband Data, Jitter Performance of Phase-Locked Loops Extracting Timing Data from) 37–58
Waveguide-Grating Couplers (Expected Behavior of) 1295–317
Waveguides and Antennas (Cross Polarization in Reflector-Type Beam) 289–316
*Wavelength Dependence of Frequency-Response Measurements in Multimode Optical Fibers* 1509–23
Webber, S. A. 1069–85
Whitfield, R. G. 663–80
Wideband Communication (Optical Fibers for) 929–55
Wyner, A. D. 343–6

Y

Yaged, B. 1553–72
Yano, D. H. 537–64

Z

0.9- to 12.4-GHz Range (Automated Network Analyzers) 691–721
Zolnoski, R. C. 537–64